

LS-PAB90-BC10

No	Output Voltage	Range Voltage	Output Current (max)	Connectors Spec.	Replacement
A	19V	18.1-19.9V	4.74A	4.8*1.7*10.7 mm DC-F	HP/COMPAQ: 18.5V/2.7A, 18.5V/3.5A, 18.5V/3.8A, 18.5V/4.9A; DELTA: 19V/2.64A; ASUS: 19V/2.64A; NEC: 19V/2.64A etc.
B	15V	14.3-15.7V	5A	6.3*3.0*10.7 mm	TOSHIBA: 15V/3A,15V/4A,15V/5A etc.
C	19V	18.1-19.9V	4.74A	5.5*2.1*10.7 mm DC-F	ACER: 19V/3.16A,19V/3.42A,19V/4.74A; LITEON: 19V/3.16A,19V/3.42A; NEC: 19V/3.16A etc.
D	19V	18.1-19.9V	4.74A	5.5*2.5*10.7 mm DC-F	IBM: 19V/4.2A; DELL: 19V/3.16A,19V/3.42A; COMPAQ/HP: 18.5V/4.9A, 19V/4.9A; DELTA: 19V/2.64A.; TOSHIBA: 19V/3.16A,19V/3.42A,19V/4.74A; ASUS: 19V/4.74A.LS:20V/3.25A; LITEON: 19V/3.16A,19V/3.42A,19V/3.95A, 19V/4.74A; NEC: 19V/2.64A,19V/3.16A; GATEWAY: 19V/3.16A,19V/3.42A, 19V/3.68A,19V/4.74A etc.
E	16V	15.2-16.8V	5A	5.5*2.5*10.7 mm DC-F	IBM: 16V/2.2A,16V/3.36A,16V/3.5A,16V/4.5A etc.
F	19V	18.1-19.9V	4.74A	5.5*3.0*10.7mm pin1.0	SAMSUNG: 19V/3.16A,19V/3.75A,19V/4.22A, 19V/4.74A etc.
G	16V	15.2-16.8V	5A	6.0*4.3*10.7 mm pin1.0	SONY: 16V/3.42A,16V/3.75A,16V/4A. FUJITSU: 16V/3.36A, 16V/3.75A etc.
H	19.5V	18.5-20.4V	4.62A	6.0*4.3*10.7mm pin1.0	SONY: 19.5V/2.7A,19.5V/3A,19.5V/4.1A,19.5V/4.7A; FUJITSU: 19V/3.16A, 19V/3.69A, 19V/4.22A etc.
I	19V	18.1-19.9V	4.74V	5.5*1.7*10.7mm DC-F	TOSHIBA: 19V/3.95A; ACER: 19V/3.42A; DELTA: 20V/3.5A etc.
J	19.5V	18.5-20.4V	4.62V	7.4*5.0*12.5 mm pin0.6	DELL: 19.5V/3.34A, 19.5V/4.62A etc.
K	20V	19.0-21.0V	4.5A	W7.3*7.4 mm	DELL: 20V/3.5A,20V/4.5A etc.
L	22V	21.9-23.1V	4A	3.5*1.35*9.5 mm	SHARP: 22V/1.8A,22V/2.04A etc.
M	20V	19.0-21.0V	4.5A	7.9*12 φ9.5 mm	IBM/LENOVO: 20V/4.5A,20V/3.25A etc.
Q	18.5V	17.6-19.4V	4.9A	7.4*5.0*12.5 mm pin0.6	HP/COMPAQ: 18.5V/3.5A,18.5V/4.9A etc.
R	12V	11.4-12.6V	5A	5.5*2.5*10.7 mm DC-F	FOR LCD etc.
S	14V	13.3-14.7V	5A	φ5.5*2.5*10.7mm DC-F	FOR LCD etc.
T	19V	18.1-19.9V	4.74A	φ4.8*1.7*10.7mm bullet	HP/COMPAQ: 18.5V4.9A,19V4.74A etc.
U	9.5V	9.0-10.0V	5A	φ4.8*1.7*10.7mm DC-F	ASUS: 9.5V2.315A etc.
V	12V	11.4-12.6V	5A	φ4.8*1.7*10.7mm DC-F	ASUS : 12V3A etc.

Input:AC 100-240V 1.8A 50-60HZ

Output: ADAPTOR:DC 9.5-22V 5A(MAX) 90W

CHARGER:DC 12.6V3A, 16.8V3A

USB:DC 5V1A(MAX) 5W